


# Motion® C5

## PRODUCT SPECIFICATIONS



<b>Processor/Cache</b>	<ul style="list-style-type: none"> <li>• Intel® Core™ 2 Duo Processor Ultra Low Voltage U7500 (2MB of L2 cache, 1.06GHz, 533MHz FSB)</li> </ul>	<b>Integrated Communications</b>	<ul style="list-style-type: none"> <li>• WiFi® 802.11 a/b/g/n</li> <li>• Integrated Intel® Wireless 4965 a/b/g/n</li> <li>• Optional Integrated Mobile Broadband</li> <li>• Integrated Class 2 Bluetooth® Module</li> </ul>
<b>Operating System</b>	<ul style="list-style-type: none"> <li>• Genuine Windows® 7 Professional (32-bit)</li> <li>• Genuine Windows® XP Tablet PC Edition (available through downgrade rights from Windows 7 or Vista Business)</li> </ul>	<b>Audio</b>	<ul style="list-style-type: none"> <li>• Motion Speak Anywhere® noise cancellation technology (with Windows XP only)</li> <li>• Multi-directional array microphone design with 2 microphones</li> <li>• Integrated speaker</li> </ul>
<b>Durability</b>	<ul style="list-style-type: none"> <li>• 3-foot drop test compliant to MIL-STD-810F</li> <li>• IP54 rated               <ul style="list-style-type: none"> <li>- Water, dust and splash resistant</li> </ul> </li> <li>• Shock-mounted display and hard drive</li> <li>• Chemically strengthened glass</li> <li>• Rubberized for shock dampening</li> <li>• Magnesium-alloy internal frame</li> <li>• Molded handle to prevent drops</li> </ul>	<b>I/O Ports</b>	<ul style="list-style-type: none"> <li>• Docking connector</li> <li>• DC power-in port with rubberized cover</li> </ul>
<b>Software</b>	<ul style="list-style-type: none"> <li>• Motion Dashboard control panel</li> <li>• Motion/Softex OmniPass™ Security software</li> <li>• Windows Journal</li> <li>• Sticky Notes</li> <li>• Motion DataGuard™</li> <li>• Acronis True Image</li> <li>• Infineon Security Platform Tools</li> <li>• Pen enabled BIOS setup</li> <li>• Intel Mobile Clinical Assistant</li> <li>• Adobe Reader</li> </ul>	<b>Embedded I/O</b>	<ul style="list-style-type: none"> <li>• 2.0 Megapixel Camera</li> <li>• Optional 1D/2D Barcode Reader</li> <li>• 13.56MHz RFID reader</li> <li>• 13.56MHz HF integrated passive RFID tag</li> </ul>
<b>Chipset</b>	<ul style="list-style-type: none"> <li>• Intel® 945GME Express</li> </ul>	<b>Security</b>	<ul style="list-style-type: none"> <li>• Integrated Fingerprint Reader with OmniPass software</li> <li>• TCG Trusted Platform Module (TPM) 1.2</li> <li>• Smart card reader (optional)               <ul style="list-style-type: none"> <li>- ISO 7816 PC/SC</li> <li>- EMV2 2000 Level 1</li> </ul> </li> <li>• ComputraceComplete (optional)</li> </ul>
<b>Display</b>	<ul style="list-style-type: none"> <li>• 10.4" XGA TFT AFFS+ LED Backlight (1024 x 768)</li> <li>• Optional View Anywhere® with durable Gorilla™ glass</li> <li>• Intel Display Power Saving Technology (DPST)</li> </ul>	<b>Dimensions</b>	<ul style="list-style-type: none"> <li>• 10.0" x 10.0" x .95" (256mm x 256mm x 24.3mm)</li> </ul>
<b>Graphics</b>	<ul style="list-style-type: none"> <li>• Intel® Graphics Media Accelerator 950</li> <li>• Rotation: 0°, 90°, 270°</li> </ul>	<b>Weight</b>	<ul style="list-style-type: none"> <li>• 3.3 lbs.<sup>1</sup> (1.50 kg)</li> </ul>
<b>Video RAM</b>	<ul style="list-style-type: none"> <li>• Maximum 256MB total with Intel Dynamic Video Memory Technology (DVMT)</li> </ul>	<b>Battery</b>	<ul style="list-style-type: none"> <li>• Battery life approximately 3.75 hours<sup>2</sup></li> <li>• Lithium-ion standard battery with 40WHr capacity</li> </ul>
<b>Audio Controller</b>	<ul style="list-style-type: none"> <li>• Intel® High Definition Audio</li> </ul>	<b>Battery Charging Time</b>	<ul style="list-style-type: none"> <li>• Standard Battery - 1.5 hours (Tablet PC on/off)<sup>3</sup></li> </ul>
<b>System Memory</b>	<ul style="list-style-type: none"> <li>• DDR2 533MHz SDRAM memory</li> <li>• Base configuration of 1GB</li> <li>• Upgradeable to maximum 2GB at point of purchase</li> </ul>	<b>System Status LEDs</b>	<ul style="list-style-type: none"> <li>• Power on/off/stand by LED ring around power button</li> <li>• Battery status LED</li> <li>• Wireless 802.11 LED</li> <li>• Bluetooth LED</li> <li>• RFID LED adjacent to RFID read trigger</li> </ul>
<b>System Storage</b>	<ul style="list-style-type: none"> <li>• 1.8" Hard Disk Drive (HDD) with 80GB capacity</li> <li>• Optional SATA Solid State Drive (SSD) with 64GB capacity</li> <li>• PCI bus master enhanced IDE</li> <li>• Supports Ultra ATA 66/100</li> </ul>	<b>AC Adapter</b>	<ul style="list-style-type: none"> <li>• 50W universal, 3-pin jack</li> <li>• 100-240V 1.5a, 50-60Hz</li> </ul>
		<b>Control Buttons</b>	<ul style="list-style-type: none"> <li>• One 5-way directional for navigation</li> <li>• One function, one Dashboard and two programmable</li> <li>• Secure Attention Sequence (SAS)</li> <li>• Camera capture</li> <li>• RFID read trigger</li> <li>• Barcode scan trigger</li> </ul>



# Motion® C5

## PRODUCT SPECIFICATIONS



### Built-in Camera

- Autofocus
- Up to 2.0 megapixel resolution
- JPG photo format with a resolution up to 1600 x 1200 pixels
- Illuminator light

### Environmental

- Temperature
  - Operation: +5°C to +35°C (+41°F to 95°F)
  - Storage: -20°C to +60°C (-4°F to 140°F)
- Humidity
  - Operating humidity: 8% to 80% without condensation
  - Storage humidity: 8% to 90% without condensation
- Altitude
  - Operation: Sea level 0 to 10K ft. sea level to 15K ft. when configured with SSD storage
  - Storage: Sea level 0 to 15K ft.
- Enclosure class

### Standards

- ACPI 3.0b compliant

### Safety

- AS/NZS 3260:1997
- AS/NZS 60950-1
- FCC/ANSI C63.41
- UL, CUL, CE (IEC/EN60950-1 A11/2004)
- CAN/CSA RSS-102
- FCC OET65 Supplement C
- ETSI EN 50392
- LVD (73/23/EEC)
- EU Directive 2002/95/EC
- EU Directive 2002/96/EC
- EU Directive 2006/66/EC and its amendments
- California Proposition 65
- Technical Instructions for Safe Transport of Dangerous Goods by Air (ICAO Doc #9284)
- Emergency Response Guidance for Aircraft incidents involving Dangerous Goods (ICAO Doc #9481)

### Regulatory

- AS/NZS 3548:1995 Class B
- AS/NZS 4771
- AS/NZS 4268
- AS/ACIF S042.1 (WCDMA/HSDPA)
- AS/ACIF S042.3 (WCDMA/HSDPA)
- AS/ACIF S042.1 (GSM/EDGE)
- AS/ACIF S042.3 (GSM/EDGE)
- CAN/CSA ICES-003 Class B
- CAN/CSA RSS-210 Issue 5
- CAN/CSA RSS-132 (1xRTT/EVDO-0/EVDO-A)
- CAN/CSA RSS-133 (1xRTT/EVDO-0/EVDO-A)
- CENELEC EN 55022 Class B (CISPR22)
- CENELEC EN 55024 (CISPR24)
- CENELEC EN 61000-3-2
- CENELEC EN 61000-3-3
- ETSI EN 301-893
- ETSI EN 300-328-2
- ETSI EN 301-489-1
- ETSI EN 301-489-3
- ETSI EN 301-489-7
- ETSI EN 301-489-17
- ETSI EN 301-489-24
- ETSI EN 300-330
- ETSI EN 301-511
- ETSI EN 301-489-1/-3
- FCC Part 15 Subpart B Class B
- FCC Part 15 Subpart C (2.4Ghz)
- FCC Part 15 Subpart E (5Ghz)
- FCC Part 22 H (1xRTT/EVDO-0/EVDO-A)
- FCC Part 24 E (1xRTT/EVDO-0/EVDO-A)
- R&TTE (89/336/EEC) & R&TTE (99/5/EC)

### Warranty

- Standard 1-year field-ready warranty
- 3-year option available

For more information and localized websites, please visit [www.MotionComputing.com](http://www.MotionComputing.com)

<sup>1</sup>Weight represents approximate system weight measured with a 40Whr battery. Actual system weight may vary depending on component and manufacturing variability.

<sup>2</sup>With SSD and 2GB RAM. Battery life is dependent on actual wireless radio usage and power settings.

<sup>3</sup>Approximate charging time. Validated charging from 5% to 90% with system on or system off.